

PVC SCHEDULE 40 CONDUIT

Size	Length	Outside Diameter	Inside Diameter	Wall Thickness	Bell Length	Lift Quantity	
						Pieces	Feet
1/2"	10'	0.840	0.622	0.109	1.00	600	6,000
	20'	0.840	0.622	0.109	1.00	600	12,000
3/4"	10'	1.050	0.824	0.113	1.25	440	4,400
	20'	1.050	0.824	0.113	1.25	440	8,800
1"	10'	1.315	1.049	0.133	1.50	360	3,600
	20'	1.315	1.049	0.133	1.50	360	7,200
1-1/4"	10'	1.660	1.380	0.140	1.75	330	3,300
	20'	1.660	1.380	0.140	1.75	330	6,600
1-1/2"	10'	1.900	1.610	0.145	2.50	259	2,590
	20'	1.900	1.610	0.145	2.50	259	5,180
2"	10'	2.375	2.067	0.154	2.75	167	1,670
	20'	2.375	2.067	0.154	2.75	167	3,340
2-1/2"	10'	2.875	2.469	0.203	2.00	93	930
	20'	2.875	2.469	0.203	2.00	93	1,860
3"	10'	3.500	3.068	0.216	4.00	75	750
	20'	3.500	3.068	0.216	4.00	75	1,500
4"	10'	4.500	4.026	0.237	4.75	48	480
	20'	4.500	4.026	0.237	4.75	48	960
6"	10'	6.625	6.065	0.280	6.50	20	200
	20'	6.625	6.065	0.280	6.50	20	400

SPECIFICATIONS:

- ICC-ES Listed (File PMG-1782)
- Conforms to UL 651 & NEMA TC 2
- Rated for 90° C Cable
- Sunlight and Corrosion Resistant

