

CPVC SDR 11 COPPER TUBE SIZE (CTS) HOT & COLD PIPE

Size	Length	Item #	Average O.D.	Min. Wall Thickness	Pieces Per Lift	Feet Per Lift
1/2"	5'	CTS-01205	0.625	0.068	500	2,500
	10'	CTS-01210	0.625	0.068	1,000	10,000
	20'	CTS-01220	0.625	0.068	1,000	20,000
3/4"	5'	CTS-03405	0.875	0.080	250	1,250
	10'	CTS-03410	0.875	0.080	500	5,000
	20'	CTS-03420	0.875	0.080	500	10,000
1"	5'	CTS-10005	1.125	0.102	240	1,200
	10'	CTS-10010	1.125	0.102	480	4,800
	20'	CTS-10020	1.125	0.102	480	9,600
1-1/4"	10'	CTS-11410	1.375	0.125	250	2,500
	20'	CTS-11420	1.375	0.125	250	5,000
1-1/2"	10'	CTS-11210	1.625	0.148	225	2,250
	20'	CTS-11220	1.625	0.148	225	4,500
2"	10'	CTS-20010	2.125	0.193	120	1,200
	20'	CTS-20020	2.125	0.193	120	2,400

SPECIFICATIONS:

Product Standards	ASTM D2846, CSA B137.6, NSF/ANSI 14, NSF/ANSI 61
Material Standard	ASTM D1784, Cell Class 2-4-4-4-8
Pressure Rating	100 PSI @ 180° F / 400 PSI @ 73° F
Temperature Rating	180° F (Max Operating Temperature)
End Finish	Plain End
Listings	NSF File 19505 ICC-ES File PMG-1322* (ASTM E84 & UL 723) *Listing for Flame Spread and Surface Burning Characteristics

