

ABS SCHEDULE 40 CELLULAR CORE DWV PIPE

Size	Length	Item #	Average O.D.	Min. Wall Thickness	Pieces Per Lift	Feet Per Lift
1-1/2"	10'	ACC-11210	1.905	0.145	259	2,590
	12'	ACC-11212	1.905	0.145	221	2,652
	20'	ACC-11220	1.905	0.145	259	5,180
2"	10'	ACC-20010	2.380	0.154	167	1,670
	12'	ACC-20012	2.380	0.154	176	2,112
	20'	ACC-20020	2.380	0.154	167	3,340
3"	10'	ACC-30010	3.507	0.216	75	750
	12'	ACC-30012	3.507	0.216	78	936
	20'	ACC-30020	3.507	0.216	75	1,500
4"	10'	ACC-40010	4.507	0.237	48	480
	12'	ACC-40012	4.507	0.237	60	720
	20'	ACC-40020	4.507	0.237	48	960
6"	10'	ACC-60010	6.625	0.280	20	200
	12'	ACC-60012	6.625	0.280	18	216
	20'	ACC-60020	6.625	0.280	20	400

SPECIFICATIONS:

Product Standards	ASTM F628, NSF/ANSI 14
Material Standard	ASTM D3965, Cell Class 4-2-2-2-2
Pressure Rating	For Non-Pressure Use Only
Temperature Rating	-40° F to 140° F
End Finish	Plain End
Listings	IAPMO File 2723 ICC-ES File PMG-1577

