

**PRODUCT SPECIFICATION**

**SCOPE**

This specification covers ABS DWV fittings used in sanitary drain, waste, and vent (DWV), sewer, and storm drainage applications. This system is intended for non-pressure applications where the operating temperature will not exceed 140° F.

**SPECIFICATION**

Fittings shall be manufactured from virgin ABS compounds with a cell class of 32222 as identified in ASTM D3965. Injection molded ABS DWV fittings shall conform to ASTM D2661. All systems shall utilize a separate waste and vent system. Fittings shall conform to NSF Standard 14.

**INSTALLATION**

Installation shall comply with the latest instructions published by Genova and shall conform to all applicable codes and requirements. Solvent cement joints shall be made with solvent cement conforming to ASTM D2235. The system of installation shall be protected from chemical agents, fire-stopping materials, thread sealant, or other aggressive chemical agents not compatible with ABS compounds. The system shall be hydrostatically tested after installation.

<b>Sizes</b>	1-1/2", 2", 3", 4", 6"
<b>Color</b>	Black
<b>Product Standard</b>	ASTM D2661
<b>Material Standard</b>	ASTM D3965
<b>Fitting Patterns</b>	ASTM D3311
<b>Certifications</b>	IAPMO 1909 ICC-ES PMG-1577

